

SEPTIK 360

BIODEGRADER FOR SEPTIC TANKS AND CHEMICAL TOILETS



BENEFITS

- Neutral pH
- Environmental friendliness (in relation to BOD / COD)
- Non-agressive / surface friendly, does not damage surfaces or equipment
- Highly concentrated product
- Highly performance product
- Continuous cleaning action
- No harmful vapors
- Odor elimination



PHYSICO-CHEMICAL FEATURES

Aspect : Blue liquid
Perfume : Mint
Density : 1.00 - 1.02
pH : 7.00 - 8.00

PACKAGINGS

1L flask - Réf. 18250010



*Product for professional use only.
For more information please refer to
the safety data sheet.*

**Product not classified according to
the CLP regulation.**

UNE MARQUE
ORAPI
GROUP

APPLICATION

Biotechnological product for septic tanks and chemical toilets (building sites, fairs, boats, motorhomes, etc.) Reduces odour problems and the risk of blockage or overflow by degrading organic matter, toilet paper, oil, grease, etc

INSTRUCTIONS

SEPTIK 360 is ready to use. Septic tanks: pour the correct dose of SEPTIK 360 into the toilet bowl then flush.

Résidential installations		Commercial installations	
Preventive treatment			
Dosage	Frequency	Dosage	Frequency
1 to 2L	3 month	2L	1 month
Curative treatment			
Dosage	Frequency	Dosage	Frequency
1 to 1.5L	1 month	4L	1 month

Chemical toilets: drain and clean the cistern. Fill with water to prescribed level. Pour in 5ml of SEPTIK 360 for every 1L of drain pan capacity (50ml / 10L, 250ml / 50L, 500ml / 100L).

ORAPI®

225 allée des Cèdres
Parc Industriel de la Plaine de l'Ain - 01150 SAINT VULBAS - FRANCE
Tél. : +33 (0)4 74 40 20 00 – Fax : +33 (0)4 74 40 20 21
www.orapi.com